



VITA CONCORD VERTICAL CONCEPT

Vita Series

50 Δt

(75/65/20°C)

SINGLE

Height mm	Length mm	Stelrad UIN	Watts	Heat output Btu/hr
1800	444	448652b	852	2907
	592	448653b	1136	3876
	740	448654b	1420	4845

DOUBLE

Height mm	Length mm	Stelrad UIN	Watts	Heat output Btu/hr
1800	444	448655b	1254	4279
	592	448656b	1672	5705
	740	448657b	2090	7131

$\Delta t50$ is the UK's industry standard for heating outputs, which has an operating temperature of 75/65/20°C. If you have a low temperature heat source you may wish to consider $\Delta t40$ or $\Delta t30$ output (see your installer or system designer or download from www.stelrad.com).

For EN442 data, technical and installation information please visit our website: www.stelrad.com and search product downloads.

VITA CONCORD VERTICAL CONCEPT

Vita Series

WALL MOUNTING INFORMATION

All dimensions in mm.

EN 442 CERTIFICATION DATA - CETIAT TESTED IN ACCORDANCE WITH BS EN 442

Type	Vertical	
Height	1800	2000
W/m at 75/65/20	1846	2041
n-coefficients	1.31	1.31
Heated surface area (m ² /m)	4.01	4.42
Weight (kg/m)	44.2	49.4
Water contents (l/m)	14.3	16.9
Wall to tap centre (mm)	43	43

WIDTH (mm)	X (mm)	Y (mm)
310	80	1590
390	160	1590
470	240	1590
604	356	1590

