




VITA SILHOUETTE CONCEPT

Vita Series

50 Δt

(75/65/20°C)

K1



K2



Height mm	Length mm	Stelrad UIN	Heat output		Price excl VAT	Price incl VAT	Stelrad UIN	Heat output		Price excl VAT	Price incl VAT
			Watts	Btu/h				Watts	Btu/h		
600	400	51601104	348	1187	£125.76	£150.91	51602204	640	2184	£143.88	£172.66
	600	51601106	522	1781	£132.47	£158.96	51602206	961	3279	£159.43	£191.32
	800	51601108	696	2375	£142.74	£171.29	51602208	1281	4371	£170.35	£204.42
	1000	51601110	870	2968	£156.07	£187.28	51602210	1601	5463	£182.80	£219.36
	1200	51601112	1044	3562	£169.40	£203.28	51602212	1921	6554	£201.48	£241.78
	1400	51601114	1218	4156	£182.72	£219.26	51602214	2241	7646	£233.77	£280.52

$\Delta t50$ is the UK's industry standard for heating outputs, which has an operating temperature of 75/65/20°C. If you have a low temperature heat source you may wish to consider $\Delta t40$ or $\Delta t30$ output (see your installer or system designer or download from www.stelrad.com).

For EN442 data, technical and installation information please visit our website: www.stelrad.com and search product downloads.


VITA SILHOUETTE CONCEPT COMES IN RAL: A7016 ANTHRACITE GREY AND IS AVAILABLE FROM STOCK.

VITA SILHOUETTE CONCEPT

Vita Series


WALL MOUNTING AND LUG INFORMATION

All dimensions in mm. Inches in brackets.



MOUNTING BRACKETS

All dimensions in mm. Inches in brackets. Floor mounting brackets available.




Dimensions	mm	inches	mm	inches	mm	inches
Height	300	11.81	450	17.72	600	23.62
A	65	2.56	65	2.56	65	2.56
B	119	4.69	99	3.90	99	3.90
C	-	-	269	10.59	419	16.50
D	153	6.02	303	11.93	453	17.83
E	185	7.28	335	13.19	485	19.09

VITA SILHOUETTE CONCEPT


Vita Series

K1 & K2 LUG POSITIONS

All dimensions in mm. Inches in brackets.




L	K1				K2			
	A		B		C		D	
	mm	in	mm	in	mm	in	mm	in
400	117	4.60	-	-	133	5.24	-	-
500 - 1100	150	5.90	-	-	133	5.24	-	-
1200 - 1600	150	5.90	-	-	133	5.24	-	-
1800 - 2000	150	5.90	(L/2) + 17		133	5.24	L/2	



CONNECTIONS

Each radiator comes with 1/2" inlet connections as standard.


PIPING OPTIONS



VITA SILHOUETTE CONCEPT

Vita Series

PRESSURE DROP



- ① Type 11 (K1)
- ② Type 22 (K2)