

HOME

SERIES



Caliente
Rail

BRINGING RADIATOR STYLE INTO UK HOMES

50 Δ t

(75/65/20°C)

STRAIGHT SINGLE

STRAIGHT DOUBLE

Height mm	Length mm	White UIN	Colour UIN	Heat output Watts Btu/hr		White UIN	Colour UIN	Heat output Watts Btu/hr	
755	450	407501450h	407501450hc	389	1,327	407502450h	407502450hc	565	1,928
	500	407501500h	407501500hc	431	1,471	407502500h	407502500hc	626	2,136
	600	407501600h	407501600hc	517	1,764	407502600h	407502600hc	749	2,556
	750	407501750h	407501750hc	645	2,201	407502750h	407502750hc	934	3,187
1199	450	401101450h	401101450hc	615	2,098	401102450h	401102450hc	868	2,962
	500	401101500h	401101500hc	675	2,303	401102500h	401102500hc	963	3,286
	600	401101600h	401101600hc	794	2,709	401102600h	401102600hc	1,154	3,937
	750	401101750h	401101750hc	972	3,316	401102750h	401102750hc	1,441	4,917
1791	450	401701450h	401701450hc	900	3,071	401702450h	401702450hc	1,268	4,326
	500	401701500h	401701500hc	986	3,364	401702500h	401702500hc	1,402	4,784
	600	401701600h	401701600hc	1,158	3,951	401702600h	401702600hc	1,670	5,698
	750	401701750h	401701750hc	1,416	4,831	401702750h	401702750hc	2,073	7,073
2013	450	402001450h	402001450hc	1,002	3,419	402002450h	402002450hc	1,427	4,869
	500	402001500h	402001500hc	1,099	3,750	402002500h	402002500hc	1,576	5,377
	600	402001600h	402001600hc	1,294	4,415	402002600h	402002600hc	1,874	6,394
	750	402001750h	402001750hc	1,586	5,411	402002750h	402002750hc	2,321	7,919

Δ t50 is the UK's industry standard for heating outputs, which has an operating temperature of 75/65/20°C. If you have a low temperature heat source you may wish to consider Δ t40 or Δ t30 output (see your installer or system designer or download from www.stelrad.com).

For EN442 data, technical and installation information please visit our website: www.stelrad.com and search product downloads.

COLOUR OPTIONS

Comes in White as standard (RAL 9016).

Please note that once a coloured radiator has been ordered, it cannot be cancelled or returned.

CENTRE TAP TRV



UIN	Elements	UIN	Elements
14531310	CENTRE TAP TRV STRAIGHT WHITE -10MM	14531610	CENTRE TAP TRV ANGLED L CHROME -10MM
14531312	CENTRE TAP TRV STRAIGHT WHITE -1/2IN	14531612	CENTRE TAP TRV ANGLED L CHROME -1/2IN
14531315	CENTRE TAP TRV STRAIGHT WHITE -15MM	14531615	CENTRE TAP TRV ANGLED L CHROME -15MM
14531410	CENTRE TAP TRV STRAIGHT CHROME -10MM	14531710	CENTRE TAP TRV ANGLED R WHITE -10MM
14531412	CENTRE TAP TRV STRAIGHT CHROME -1/2IN	14531712	CENTRE TAP TRV ANGLED R WHITE -1/2IN
14531415	CENTRE TAP TRV STRAIGHT CHROME -15MM	14531715	CENTRE TAP TRV ANGLED R WHITE -15MM
14531510	CENTRE TAP TRV ANGLED L WHITE -10MM	14531810	CENTRE TAP TRV ANGLED R CHROME -10MM
14531512	CENTRE TAP TRV ANGLED L WHITE -1/2IN	14531812	CENTRE TAP TRV ANGLED R CHROME -1/2IN
14531515	CENTRE TAP TRV ANGLED L WHITE -15MM	14531815	CENTRE TAP TRV ANGLED R CHROME -15MM

Brackets are colour matched for White, Anthracite and Black rails; all other colours come with Chrome brackets.



WARRANTY



TRAFFIC WHITE
IN STOCK




DELIVERY WITHIN
14 WORKING DAYS

www.stelrad.com
Telephone: 0800 876 6813


SINGLE WALL MOUNTING INFORMATION

All dimensions in mm. Inches in brackets.



DOUBLE WALL MOUNTING INFORMATION

All dimensions in mm. Inches in brackets.




CONNECTIONS

Each radiator comes with 1/2" inlet connections as standard.


PIPING OPTIONS

Single and Double.



Piping options: BBOE (Bottom, Bottom, Opposite, End)

TAPPING CENTRES



EN 442 CERTIFICATION DATA - CETIAT TESTED IN ACCORDANCE WITH BS EN 442

SINGLE

Type																
Tube quantity	18	18	18	18	28	28	28	28	42	42	42	42	48	48	48	48
Height	755	755	755	755	1199	1199	1199	1199	1791	1791	1791	1791	2013	2013	2013	2013
Length	450	500	600	750	450	500	600	750	450	500	600	750	450	500	600	750
W/m at 75/65/20	389	431	517	645	615	675	794	972	900	986	1158	1416	1002	1099	1294	1586
n-coefficients	1.18	1.17	1.15	1.13	1.21	1.20	1.19	1.17	1.24	1.23	1.21	1.17	1.26	1.24	1.21	1.17
Heated surface area (m ² /m)	0.75	0.82	0.94	1.13	1.18	1.28	1.47	1.76	1.77	1.91	2.20	2.64	2.01	2.18	2.51	3.01
Weight (kg/m)	6.80	7.37	8.52	10.24	10.90	11.77	13.52	16.14	16.54	17.83	20.43	24.32	18.90	20.38	23.35	27.79
Water contents (l/m)	3.70	3.96	4.49	5.28	5.90	6.29	7.07	8.25	8.75	9.35	10.54	12.33	10.00	10.68	12.05	14.09

DOUBLE

Type																
Tube quantity	2x18	2x18	2x18	2x18	2x28	2x28	2x28	2x28	2x42	2x42	2x42	2x42	2x48	2x48	2x48	2x48
Height	755	755	755	755	1199	1199	1199	1199	1791	1791	1791	1791	2013	2013	2013	2013
Length	450	500	600	750	450	500	600	750	450	500	600	750	450	500	600	750
W/m at 75/65/20	565	626	749	934	868	963	1154	1441	1269	1402	1670	2073	1427	1576	1874	2321
n-coefficients	1.21	1.21	1.20	1.19	1.23	1.23	1.22	1.21	1.25	1.24	1.23	1.20	1.25	1.24	1.23	1.21
Heated surface area (m ² /m)	1.33	1.45	1.70	2.07	2.07	2.26	2.65	3.23	3.10	3.39	3.97	4.85	3.54	3.87	4.53	5.53
Weight (kg/m)	12.47	13.59	15.82	19.17	19.40	21.14	24.61	29.82	29.15	31.75	36.94	44.72	33.20	36.14	42.01	50.82
Water contents (l/m)	6.62	7.19	8.32	10.02	10.30	11.18	12.95	15.59	15.32	16.62	19.23	23.13	17.60	19.11	22.13	26.65
Km	4.91	5.54	6.86	9.00	6.97	7.87	9.77	12.84	9.54	10.84	13.64	18.38	10.66	12.10	15.21	20.48

55 COLOUR OPTIONS. 14-DAY LEAD TIME.

Stelrad Radiators are available in white (RAL 9016) as standard, however this radiator is **now available in a variety of colours within 14 working days.**

STANDARD COLOUR




RAL 9016
Traffic white

To request up to 5 colour samples, please email sales@stelrad.com or call **0800 876 6813** with your choices and address details.

The colours shown are reproduced as accurately as this printing process will allow.


RAL COLOURS - Satin Finish



1001
Beige



1013
Oyster white



1015
Light ivory



9001
Cream



9002
Grey white




9003
Signal white




9010
Pure white



9016
Traffic white




9018
Papyrus white



9005
Jet black



9017
Traffic black



7001
Silver grey




7011
Iron grey




7015
Slate grey



7016
Anthacite grey




7030
Stone grey




7032
Pebble grey



7035
Light grey




7036
Platinum grey



7037
Dusty grey



7038
Agate grey



7039
Quartz grey




5002
Ultramarine blue




5010
Gentian blue




5012
Light blue



5014
Pigeon blue




5015
Sky blue




5022
Night blue



RAL COLOURS (continued)




5024
Pastel blue




6005
Light moss green




6018
Yellow green




6019
Pastel green




6020
Chrome green



6027
Light green



6033
Mint turquoise



6034
Pastel turquoise




3000
Flame red



3002
Carmine red



3003
Ruby red



3005
Wine red



2003
Pastel orange



2008
Bright red orange



1004
Golden yellow




1016
Sulphur yellow




1021
Colza yellow




3015
Light pink




8014
Sepia



8017
Chocolate brown



7026
Granite



1019
Cappuccino




8028
Terra brown




9011
Graphite black


METALLIC



1247M
Bronze metallic



7001M
Silver metallic



9007M
Grey metallic

Please note: When a coloured radiator or radiators have been ordered they cannot be cancelled or returned.

For further information on RAL colours please visit
www.ralcolorchart.com